WATER MANAGEMENT Cherokee County, Kansas

The soils of the survey area are rated in the Water Management table according to limitations that affect their suitability for water management. Soils are rated for pond reservoir areas, drainage, irrigation, terraces and diversions, and grassed waterways. Restrictive features that affect each soil for the specified use is also provided in the table.

The ratings in the table are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Moderately limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Limited indicates that the soil has one or more features that are significant limitations for the specified use. The limitations can be overcome, but generally require special design, soil reclamation, or installation procedures that may result in additional expense. Fair performance and moderate to high maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Limitation class terms, such as very limited or limited, etc., limitation ratings, and numerical ratings are shown for each soil feature listed. As many as three soil features may be listed for each soil component if applicable. The overall limitation rating for the soil component is based on the most severe limitation.

Pond reservoir areas hold water behind a dam or embankment. Soils best suited to this use have low seepage potential in the upper 60 inches. The seepage potential is determined by the permeability of the soil and the depth to fractured bedrock or other permeable material. Excessive slope can affect the storage capacity of the reservoir area

Embankments, dikes, and levees are raised structures of soil material, generally less than 20 feet high, constructed to impound water or to protect land against overflow. In this table, the soils are rated as a source of material for embankment fill. The ratings apply to the soil material below the surface layer to a depth of about 5 feet. It is assumed that soil layers will be uniformly mixed and compacted during construction.

The ratings do not indicate the ability of the natural soil to support an embankment. Soil properties to a depth even greater than the height of the embankment can affect performance and safety of the embankment. Generally, deeper onsite investigation is needed to determine these properties.

Soil material in embankments must be resistant to seepage, piping, and erosion and have favorable compaction characteristics. Unfavorable features include less than 5 feet of suitable material and a high content of stones or boulders, organic matter, or salts or sodium. A high water table affects theamount of usable material. It also affects traffic ability.

Aquifer-fed excavated ponds are pits or dugouts that extend to a ground-water aquifer or to a depth below a permanent water table. Excluded are ponds that are fed only by surface runoff and embankment ponds that impound water 3 feet or more above the original surface. Excavated ponds are affected by depth to a permanent water table, permeability of the aquifer, and quality of the water as inferred from the salinity of the soil. Depth to bedrock and the content of large stones affect the ease of excavation.

Drainage is the removal of excess surface and subsurface water from the soil. How easily and effectively the soil is drained depends on the depth to bedrock, to a cemented pan, or to other layers that affect the rate of water movement; permeability; depth to a high water table or depth of standing water if the soil is subject to ponding; slope; susceptibility to flooding; subsidence of organic layers; and the potential for frost action. Excavating and grading and the stability of ditch banks are affected by depth to bedrock or to a cemented pan, large stones, slope, and the hazard of cutbanks caving. The productivity of the soil after drainage is adversely affected by extreme acidity or by toxic substances in the root zone, such as salts, sodium, and sulfur. Availability of drainage outlets is not considered in the ratings.

Irrigation is the controlled application of water to supplement rainfall and support plant growth. The design and management of an irrigation system are affected by depth to the water table, the need for drainage, flooding, available water capacity, intake rate, permeability, erosion hazard, and slope. The construction of a system is affected by large stones and depth to bedrock or to a cemented pan. The performance of a system is affected by the depth of the root zone, the amount of salts or sodium, and soil reaction.

Terraces and diversions are embankments or a combination of channels and ridges constructed across a slope to control erosion and conserve moisture by intercepting runoff. Slope, wetness, large stones, and depth to bedrock or to a cemented pan affect the construction of terraces and diversions. A restricted rooting depth, a very limited hazard of wind erosion or water erosion, an excessively coarse texture, and restricted permeability adversely affect maintenance.

Grassed waterways are natural or constructed channels, generally broad and shallow, which conduct surface water to outlets at a non-erosive velocity. Large stones, wetness, slope, and depth to bedrock or to a cemented pan affect the construction of grassed waterways. A hazard of wind erosion, low available water capacity, restricted rooting depth, toxic substances such as salts and sodium, and restricted permeability adversely affect the growth and maintenance of the grass after construction.

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

	Features affecting							
Map symbol and soil name	Drainage	Irrigation	Terraces and diversions	Grassed waterways				
	Limitation: percs slowly	Limitation: slow intake wetness	Limitation: percs slowly wetness	Limitation: percs slowly wetness				
Be: Bates		Limitation: depth to rock	Limitation: depth to rock	Limitation: depth to rock				
Bf: Bates	Limitation: deep to water	Limitation: slope depth to rock	Limitation: depth to rock	Limitation: depth to rock				
Bh: Bates	Limitation: deep to water	Limitation: slope	Limitation: depth to rock	Limitation: depth to rock				
Collinsville	Limitation: deep to water	depth to rock Limitation: large stones slope droughty	Limitation: large stones slope depth to rock	Limitation: large stones slope droughty				
Bo: Bolivar	Limitation: deep to water	Limitation: slope soil blowing	Limitation: slope soil blowing	Limitation: slope depth to rock				
Hector	Limitation: deep to water	depth to rock Limitation: slope soil blowing droughty	depth to rock Limitation: slope soil blowing depth to rock	Limitation: slope depth to rock droughty				
Br: Brazilton		Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly				
Cd: Catoosa	Limitation: deep to water	Limitation: erodes easily depth to rock						
Ce: Cherokee	Limitation: percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness				
Ck: Clarksville	Limitation: deep to water	Limitation: large stones slope droughty	Limitation: large stones slope	Limitation: large stones slope droughty				
Db: Dennis	Limitation: percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness				
Du: Dumps En:								
Eram	Limitation: percs slowly slope depth to rock	Limitation: percs slowly slope wetness	Limitation: erodes easily wetness depth to rock	Limitation: erodes easily wetness depth to rock				
Es: Eram	Limitation: percs slowly slope depth to rock	Limitation: percs slowly slope	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope				
Shidler	Limitation: deep to water	Limitation:	Limitation: large stones	Limitation: large stones				
Ge: Gerald		Limitation: percs slowly wetness droughty	Limitation: erodes easily rooting depth wetness	Limitation: erodes easily				
He: Hepler	Limitation: flooding	Limitation: erodes easily flooding wetness	Limitation: erodes easily wetness	Limitation: erodes easily wetness				
	Limitation: flooding	Limitation: erodes easily flooding wetness	Limitation: erodes easily wetness	Limitation: erodes easily wetness				
Ka: Kanima	Limitation: deep to water	Limitation: slope droughty	Favorable	Limitation: droughty				

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

	Features affecting							
Map symbol and soil name	Drainage	Irrigation	Terraces and diversions	Grassed waterways				
Kn:								
Kanima	Limitation: deep to water	Limitation: slope droughty	Limitation: slope	Limitation: slope droughty				
Lņ:								
Lanton	flooding percs slowly		Limitation: erodes easily wetness	Limitation: erodes easily percs slowly wetness				
M-W: Miscellaneous Water								
Ns:			l					
Nixa		Limitation: percs slowly slope droughty	Limitation: percs slowly rooting depth	Limitation: percs slowly rooting depth droughty				
Os:								
Osage	Limitation: flooding percs slowly	Limitation: slow intake wetness droughty	Limitation: percs slowly wetness	Limitation: percs slowly wetness droughty				
Pr:								
Parsons	Limitation: percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness				
Qu:								
Quarries								
Se: Secesh	Limitation: deep to water	Favorable	Limitation: large stones	Limitation: large stones				
Sf:								
Secesh	Limitation: deep to water	Limitation: flooding	Limitation: large stones	Limitation: large stones				
To: Taloka	Limitation: percs slowly	percs slowly	Limitation: erodes easily percs slowly	percs slowly				
		wetness	wetness	wetness				
Tt: Tonti	Limitation: deep to water	Limitation: percs slowly slope droughty	Limitation: erodes easily percs slowly rooting depth	Limitation: erodes easily rooting depth droughty				
Vb:		1		1				
Verdigris	Limitation: deep to water	Limitation: flooding	Favorable	Favorable				
W:								
Water Wa:								
Waben	Limitation: deep to water	Limitation: slope droughty	Favorable	Limitation: droughty				
Za:	Timitati	 Timitati	Timitati	 Timitati				
Zaar	Limitation: percs slowly	Limitation: percs slowly slow intake wetness	Limitation: percs slowly wetness	Limitation: percs slowly wetness				

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol Pct and soil name of map unit		Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer-fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
037ZA: Zaar	96	Not limited		Very limited Depth to saturated zone Hard to pack	1.00	Very limited Deep to water	1.00
Be: Bates	85	Somewhat limited Seepage Depth to bedrock	0.70	Somewhat limited Thin layer	0.74	Very limited Deep to water	1.00
Bf: Bates	85	Somewhat limited Depth to bedrock Seepage	0.30	Somewhat limited Thin layer	0.98	Very limited Deep to water	1.00
Bh: Bates	45	Somewhat limited Depth to bedrock Seepage	0.19	Somewhat limited Thin layer	0.93	Very limited Deep to water	1.00
Collinsville	40	Very limited Seepage Depth to bedrock	1.00	Very limited Thin layer Piping Seepage	1.00 1.00 0.09	Very limited Deep to water	1.00
Bo: Bolivar	55	Somewhat limited Depth to bedrock Seepage	0.22	Somewhat limited Piping Thin layer	0.90	Very limited Deep to water	1.00
Hector	40	Very limited Seepage Depth to bedrock	1.00	Very limited Thin layer Piping Seepage	1.00 1.00 0.09	Very limited Deep to water	1.00
Br: Brazilton	100	Somewhat limited Seepage	0.05	Somewhat limited Seepage Hard to pack	0.45	Very limited Deep to water	1.00
Cd: Catoosa	85	Somewhat limited Depth to bedrock Seepage	0.91	Somewhat limited Thin layer Hard to pack	0.91	Very limited Deep to water	1.00
Ce: Cherokee	100	Not limited		Very limited Depth to saturated zone Hard to pack	1.00	Very limited Deep to water	1.00
Ck: Clarksville	100	Very limited Seepage Slope	1.00	Somewhat limited Seepage	0.25	Very limited Deep to water	1.00
Db: Dennis	90	Somewhat limited Seepage	0.05	Very limited Depth to saturated zone Hard to pack	1.00	Very limited Deep to water	1.00
Du: Dumps	100	Not rated		Not rated		Not rated	
En: Eram	90	Somewhat limited Depth to bedrock	0.08	Very limited Depth to saturated zone Hard to pack Thin layer	1.00 0.97 0.81	Very limited Deep to water	1.00
Es: Eram	50	Somewhat limited Depth to bedrock	0.23	Very limited Depth to saturated zone Thin layer	1.00	Very limited Deep to water	1.00

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit Pond Reservoir Area Embankments, Dikes, and Levees		and	Excavated Ponds (Aquifer- fed)			
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Shidler	40	Very limited Seepage Depth to bedrock	1.00	Hard to pack Very limited Thin layer Piping	0.92 1.00 0.08	Very limited Deep to water	1.00
Ge: Gerald	90	Not limited		Very limited Depth to saturated zone	1.00	Very limited Deep to water	1.00
He: Hepler	95	Somewhat limited Seepage	0.70	Very limited Depth to saturated zone Piping		Somewhat limited Slow refill Cutbanks cave	0.30
Hf: Hepler	95	Somewhat limited Seepage	0.70	Very limited Depth to saturated zone Piping	1.00	Somewhat limited Slow refill Cutbanks cave Deep to water	0.30 0.10 0.00
Ka: Kanima	100	Somewhat limited Seepage	0.70	Somewhat limited Content of large stones	0.00	Very limited Deep to water	1.00
Kn: Kanima	95	Somewhat limited Seepage Slope	0.70	Somewhat limited Content of large stones	0.00	Very limited Deep to water	1.00
Ln: Lanton	95	Somewhat limited Seepage	0.70	Very limited Depth to saturated zone	1.00	Very limited Deep to water	1.00
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Ns: Nixa	95	Not limited		Somewhat limited Seepage	0.12	Very limited Deep to water	1.00
Os: Osage	90	Not limited		Very limited Ponding Depth to saturated zone Hard to pack	1.00	Very limited Slow refill Cutbanks cave	1.00
Pr: Parsons	90	Not limited		Very limited Depth to saturated zone	1.00	Very limited Deep to water	1.00
Qu: Quarries	100	Not rated		Not rated		Not rated	
Se: Secesh	95	Very limited Seepage	1.00	Not limited		Very limited Deep to water	1.00
Sf: Secesh	91	Very limited Seepage	1.00	Not limited		Very limited Deep to water	1.00
To: Taloka	90	Somewhat limited Seepage	0.70	Very limited Depth to saturated zone	1.00	Very limited Deep to water	1.00

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer-fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Tt: Tonti	95	Not limited		Somewhat limited Seepage	0.15	Very limited Deep to water	1.00
Vb: Verdigris	95	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.16	Very limited Deep to water	1.00
W: Water	100	Not rated		Not rated		Not rated	
Wa: Waben	90	Somewhat limited Seepage	0.70	Somewhat limited Seepage	0.07	Very limited Deep to water	1.00
Za: Zaar	90	Not limited		Very limited Depth to saturated zone Hard to pack	1.00	Very limited Deep to water	1.00